

HARSHAD

SAFETY VALVE MANUFACTURER



ISO 9001 CERTIFIED COMPANY

SAFETY VALVE SERIES # 002

CE 1128

INLET SIZE	1/2" TO 4"
OUTLET SIZE	FREE (ATMOSPHERIC DISCHARGE)
SET PRESSURE RANGE	0.5BARG TO 19BARG
END CONNECTION	THREAD END (BSP, BSPT & NPT)
TEMPERATURE RANGE	-20°C TO 300°C
ORIFICE AREA	"D" TO "Q"
BODY	CAST STEEL GUN METAL STAINLESS STEEL
INTERNAL PARTS (NOZZLE & DISC)	GUN METAL STAINLESS STEEL
SPRING	SPRING STEEL (IS 4454) STAINLESS STEEL (SS302)
SEAT	METAL SEAT
APPLICATION / MEDIUM	AIR NITROGEN GAS STEAM
APPLICABLE CODE & STD	API520, API527, ASME 16.34 EN ISO 4126 PART 1, ASME SEC.VIII PTC-25



MODEL # 002-12-DN50-BM
REV.2/ 02.2025

HARSHAD ENGINEERING WORKS

WORK & OFFICE ADDRESS :-
S-120 TO S-125, VIVEKANAND
INDUSTRIAL ESTATE, NEAR RAKHIAL
CROSS ROAD, RAKHIAL, AHMEDABAD -
380023. GUJARAT, INDIA.

PH # :+91-9879355077, 9825035792
EMAIL : hew@hewvalve.com
WEB 1 : www.hewvalve.com
WEB 2 : www.hewsafetyvalves.com