

HARSHAD

SAFETY VALVE MANUFACTURER



ISO 9001 CERTIFIED COMPANY

SAFETY RELIEF VALVE SERIES # 006

CE 1128

INLET SIZE	1" TO 6"
OUTLET SIZE	2" TO 8"
SET PRESSURE RANGE	1BARG TO 255BARG
END CONNECTION	FLANGE END (ANSI B 16.5 R.F.) (150# TO 1500#)
TEMPERATURE RANGE	-196°C TO 538°C
ORIFICE AREA	"D" TO "Q"
BODY & BONNET	CAST STEEL & STAINLESS STEEL
INTERNAL PARTS (NOZZLE, DISC & SPINDLE)	SS316 & SS304
SPRING	SPRING STEEL (IS 4454) STAINLESS STEEL (SS302 / SS316) INCONEL (CX750) ALLOY STEEL (50CRV4)
SEAT	METAL, PLASTIC & VITON RUBBER SEAT
APPLICATION / MEDIUM	AIR OR GAS STEAM LIQUID
APPLICABLE CODE & STD	API 526, API520, API527, API 521, ISO 4126 PART 1, API 576 ASME SEC.VIII PTC-25, ASME 16.34



REV.2 / 02.2025

HARSHAD ENGINEERING WORKS

WORK & OFFICE ADDRESS :-
S-120 TO S-125, VIVEKANAND
INDUSTRIAL ESTATE, NEAR RAKHIAL
CROSS ROAD, RAKHIAL, AHMEDABAD -
380023. GUJARAT, INDIA.

PH # :+91-9879355077, 9825035792
EMAIL : hew@hewvalve.com
WEB 1 : www.hewvalve.com
WEB 2 : www.hewsafetyvalves.com