

# HARSHAD

SAFETY VALVE MANUFACTURER



ISO 9001 CERTIFIED COMPANY

## SAFETY VALVE 1128

### SERIES # 008

INLET SIZE	1/2" TO 2"
OUTLET SIZE	1", 1-1/2" & 2"
SET PRESSURE RANGE	1BARG TO 19BARG
END CONNECTION	THREAD END (BSP, BSPT & NPT)
TEMPERATURE RANGE	-59°C TO 300°C
SEAT	METAL SEAT
ORIFICE AREA	"D" TO "J"
BODY & BONNET	CAST STEEL GUN METAL STAINLESS STEEL
INTERNAL PARTS (NOZZLE, DISC & SPINDLE)	SS304, SS316 & GUN METAL
SPRING	SPRING STEEL (IS 4454) STAINLESS STEEL (SS302) INCONEL (X750)
APPLICATION / MEDIUM	AIR, GAS, VAPOR STEAM LIQUID
APPLICABLE CODE & STD	ASME 16.34, API527, API 520 ISO 4126 PART 1, ASME SEC.VIII DIV.1



**THREAD END  
MALE X FEMALE**

**REV.02 / 02.2025**

## HARSHAD ENGINEERING WORKS

**WORK & OFFICE ADDRESS :-**  
S-120 TO S-125, VIVEKANAND  
INDUSTRIAL ESTATE, NEAR RAKHIAL  
CROSS ROAD, RAKHIAL, AHMEDABAD -  
380023. GUJARAT, INDIA.

PH # :+91-9879355077, 9825035792  
EMAIL : hew@hewvalve.com  
WEB 1 : www.hewvalve.com  
WEB 2 : www.hewsafetyvalves.com