

HARSHAD

SAFETY VALVE MANUFACTURER



ISO 9001 CERTIFIED COMPANY

THERMAL RELIEF VALVE

SERIES # 088

CE 1128

INLET SIZE	1/2", 3/4", 1" & 1-1/2"
OUTLET SIZE	1", 1-1/2"
SET PRESSURE RANGE	1BARG TO 255BARG
END CONNECTION	THREAD END (BSP-F & NPT-F)
TEMPERATURE RANGE	-59°C TO 300°C
BODY & BONNET	CAST STEEL STAINLESS STEEL SUPER DUPLEX
INTERNAL PARTS (NOZZLE, DISC & SPINDLE)	SS316 & SS304 SUPER DUPLEX
SPRING	SPRING STEEL (IS 4454) STAINLESS STEEL (SS302) INCONEL (X750)
APPLICATION / MEDIUM	AIR OR GAS VAPOUR LIQUID
APPLICABLE CODE & STD	ASME 16.4, API520, API527, ISO 4126 PART 1, ASME SEC.VIII DIV.1
SEAT	METAL VITON RUBBER PLASTIC



**THREAD END
FEMALE X FEMALE**

REV.02 / 02.2025

HARSHAD ENGINEERING WORKS

WORK & OFFICE ADDRESS :-
S-120 TO S-125, VIVEKANAND
INDUSTRIAL ESTATE, NEAR RAKHIAL
CROSS ROAD, RAKHIAL, AHMEDABAD -
380023. GUJARAT, INDIA.

PH # : +91-9879355077, 9825035792
EMAIL : hew@hewvalve.com
WEB 1 : www.hewvalve.com
WEB 2 : www.hewsafetyvalves.com